VERSALIFTVDTL175-F



VDTL175-F - Mercedes-Benz Sprinter



Emergency operation from ground (valve-bank mounted on pedestal)

Better performance (additional working height and outreach)

Designed to support up to 265 kg (depending on the stability of the vehicle)

■ Length: 7,200 mm ■ Height: 3,490 mm

■ Wheelbase: 3,665 mm






























8.5 m / 6.6 m 120 kg / 230 kg

2 man Eco

A-frame

3,500 kg

Diagramme(s)



Options

LED ceiling lights (in the load area) Safety stripes (red/white) Reversing camera Removable LED spotlight Display in the upper control panel Bucket rotator (2 x 90°) Display in the upper control panel Limited working area without outriggers



The shaped profile ultra high strength steel booms provide improved rigidity, stiffness and performance



Turret/knuckle tail swing within the mirrors



Workshop interior (optional)



LMC (Load Moment Controls): Variable outreach and up to 2 actions at a time (1 per joystick)

Notes

Technical information is subject to change without prior notice. Images may show optional equipment. Installations and/or options may not be available in your specific region.

- * Depending on the vehicle.
- ** Max payload with a driver, a passenger and a full tank of fuel (220 kg added to the installation weight).

Distributor

Versalift International

Soendervang 3, 9640 Farsoe Denmark

+45 9863 2433 sales@versalift.dk versaliftinternational.com

